

FLEXIBURNER DUO

EVIDENTIAL RECORDER



- TWO CHANNEL MULTI FUNCTION DVR
- SILENT OPERATION
- SUPPORTS MPEG2, MPEG4 AND DIV X CODECS
- LOCAL REVIEW AND MONITORING WHILE RECORDING
- NETWORK CAPABLE
- CONTROL INTERFACE FOR PTZ CAMERAS
- RECORDING CAPABILITY TO EXTERNAL USB HARD DRIVE
- RUNS TVM AWARD WINNING AWARD MOTION DETECTION SOFTWARE

OPERATIONAL BENEFITS

- NO MORE WRESTLING WITH DVD'S AT THE OP
- ARCHIVE FOOTAGE FROM SAFETY OF THE OFFICE
- VASTLY INCREASED RECORD TIME
- MASSIVELY REDUCED "POST ANALYSIS" TIME
- WHEN NETWORK ENABLED - PROVIDES REAL TIME ALERTS
- PROVIDES RS232 INTERFACE FOR PTZ CAMERAS
- FULLY SCALABLE AND UPGRADEABLE REDUCING EQUIPMENT REDUNDANCY



The Association of
Police and Public
Security Suppliers



Winner of the APPSS Equipment & Technology Innovation Awards

Awarded at HOSDB 2009

OPERATIONALLY PROVEN TECHNOLOGY

FLEXIBURNER DUO

EVIDENTIAL RECORDER

TECHNICAL SPECS

Dimensions & Power	
Size mm (W x D x H)	270 X 195 X 102
Housing Material	Extruded Aluminium Heat Sink
Finish	Powder Coat Black
Voltage	
	12 – 30 Volts DC
Operating Temperature	
	-5° C to 55° C
Input & Output	
2	BNC Input
2	BNC Output
1	RS232 / 485 (44 pin D Connector c/w Break Out Lead)
2	Ethernet
6	USB
1	VGA
1	12v Power Input
1	12v sw Output
1	3.5mm Mic Input
Recorder	
DVD Requirement	DVD -R
Burn Rate	8x
Typical Burn Time	10 – 15 Minutes
Hard Drive	250 GB Internal (Optional External USB HDD up to 500GB)
Video	
Codec	MPEG2, MPEG2 Time-lapse, MPEG4, Div X
Resolution	640 x 480 (352 x 240 Option on MPEG4 & Div X)
Video Standards	PAL (NTSC on Request)
Video Quality	Very High, High, Medium, Low
Frame Rate	1, 2, 3, 4, 5, 10, 15, 20, 25
Additional Features	
Camera Control	Optional PTZ Control Via RS 232 & RS 485 Interface Protocols Include: Sonic Communications, David Horn, Pace Systems & Pelco "D"
Optional	Award Winning – Differentiating Optical Motion Detection
Supplied Accessories	
	240 / 12 Volt Mains PSU Open Ended 12 Volt Power Cable 10 Pk DVD -R