

LEADERS IN INTELLIGENT
SURVEILLANCE MANAGEMENT SYSTEMS

TransVisual Media
TransVisual Media
TransVisual Media
TransVisual Media

FLEXIBURNER² HYBRID

ANALOGUE & IP RECORDER



- IP OR ANALOGUE RECORDER
- MOBILE OR VEHICLE BORNE VIDEO SURVEILLANCE SOLUTION
- RAPID DEPLOYMENT
- INCORPORATES FLEXIBURNER 2 EVIDENTIAL RECORDER
- EXTERNAL CONNECTION PANEL
- SIMPLE TOUCHSCREEN USER INTERFACE
- FULL FUNCTIONALITY CONTROL OVER IP/3G NETWORKS
- 250 GB INTERNAL DRIVE
- EXTERNAL USB HARD DRIVE CAPABILITY (HOTSWAP)
- OPTIONAL MOTION DETECTION SOFTWARE FUNCTIONALITY ENABLES REAL TIME ALERTING OVER IP/3G NETWORKS



The Association of
Police and Public
Security Suppliers



EQUIPMENT AND TECHNOLOGY INNOVATION
**AWARDS TVM 2009
WINNER**

OPERATIONALLY PROVEN TECHNOLOGY

Tel: 02476 100012, Fax: 02476 100014, E-Mail: sales@transvisualmedia.com, website: www.transvisualmedia.com

TRANSVISUAL MEDIA LTD, UNIT 6, VANGUARD CENTRE, WARWICK SCIENCE PARK, SIR WILLIAM LYONS ROAD, COVENTRY, ENGLAND, CV4 7EZ

FlexiBurner2 Hybrid Technical Specifications

Dimensions and power

Size mm	(W x D x H) – 524 x 428 x 206
Housing material	Ruggedised peli case
Weight	14 Kg
Voltage	10-18v
Current	2.4 amps
Op temp	5 to 55

Input & Output

BNC Input	x1
BNC output	x1
RS232 Serial port	x1
Ethernet ports	x2
USB external	x2
USB Internal	x2
Touchscreen connection	x1
Input	12v
Output	12v

Recorder

DVD requirement	DVD -R
Burn rate	8x
Typical burn time	10 – 15 minutes
Hard drive	250Gb Internal (Optional external USB HDD up to 1 TB)

Video

Codec	MPEG2, MPEG2 Time-lapse, Mpeg4, Div X
Resolution	640 x 480, (352x 240 option on Mpeg4 and Div X)
Video Standards	NTSC on request
Frame rate	1,2,3,4,5,10,15,20,25 frames per second

IP Video functions

Supports motion detection and recording from RTSP compliant IP cameras (eg. Axis, Sony)
PTZ controls for Axis and Sony IP cameras

Additional Features

Camera control	Optional PTZ control Via RS232 interface. Protocols include: Sonic communications, Pace Systems, Sony Visca. SMS status reports (daily status, power on, hard drive 80%)
----------------	---

Supplied accessories

240 / 12v Power cable. Open ended 12v power cable.